

扬州三菱电子有限公司
规格书

客户 _____

型号 MXG(Y)25

地址：江苏省扬州市南通西路 6 号

电话：0514-87344294

传真：0514-87310017

E— mail: SL you and me @ 163.com

<http://www.YZSLDZ.com>

MXG(Y)25 技术资料

特点:

- 金属化三氧化二铝陶瓷绝缘, 传热性好。
- 高温焊料焊接, 有利于可靠性。

典型应用:

- 发电机

V_{RSM} (V)	V_{RRM} (V)	I_O (AV) =25A (sin 180° Tc=100°C)
900	800	MXG(Y)25-8
1300	1200	MXG(Y)25 -12
1500	1400	MXG(Y)25 -14
1700	1600	MXG(Y)25 -16
1900	1800	MXG(Y)25 -18
2100	2000	MXG(Y)25 -20
2500	2400	MXG(Y)25-24

符号	测试条件	数值	单位
I_O (AV)	Tc=100°C, 三相全波	25	A
I_{FSM}	Ta=25°C, 10ms	300	A
I^2t	Ta=25°C, 10ms	0.005×300^2	A ² S
V_{FM}	$I_{FM}=25A, Ta=25°C$	1.30	V
V_{F0}	Tj=150°C	0.88	V
r_F	Tj=150°C	10	mΩ
I_{R1}	Ta=25°C, $V_R=V_{RSM}$	20	μA
I_{R2}	Ta=150°C, $V_R=V_{RRM}$	2	mA
Rjc		0.90	°C/W
Tstg		-40~+150	°C
Viso	Ac, 50HZ, 正弦波, 1min	2500	V
Ms	散热器安装力矩	2.5	N·m





